

Model Number:

UPC.FTPJP4935LL



- Koneksi setiap unit memiliki stabilitas yang lebih tinggi dan handal
- Fungsi sinyal dan kontrol gambar yang lebih stabil dan akurat, untuk menayangkan citra yang lebih baik
- Resolusi tinggi, kontras tinggi, sudut pandang sangat lebar dan desain sambungan yang rapat

- ◇ Excellent HD image.
- ◇ Super narrow bezel design 3.5 mm.
- ◇ HD 1920 × 1080 resolution support.
- ◇ Easy 178 degrees viewing angles.



Specifications	Panel Size	49"
	Display Mode	IPS LG Panel
	Max Resolution Support	1920 x 1080
	Pixel Pitch	0.5592 (h) x 0.5592 (v) mm
	Display Colors	8 Bit, 16.7 M
	Brightness (nits)	500 cd/m2
	Contrast	1300 : 1
	Visual Angle (H/V)	178°(H) / 178°(V)
	Narrow Bezel	3.5 mm
	Response Time	≤6 ms
	Lifetime	>100,000 hrs
	Aspect ratio	16:9 (H:V)
	Video Standard	PAL, NTSC
	Standby Power Consumption	≤3 W
	Maximum Power	250 W
	Power Supply	100~240 VAC, 50/60 Hz
	Operating temperature	0°C ~ 50°C
	Storage temperature	-20°C ~ 65°C
	Working Humidity	10% ~ 90%
	Control Interface	RJ45 (by RS232)
	Digital signal input	CVBS, HDMI, VGA, DVI, USB
	Digital signal output	LVDS, RJ45
	Border Dimension	Top: 0.9mm; Bottom 0.9mm; Left: 0.9mm; Right: 0.9mm
	Installation way	Wall mount, floor standing mount, hanging mount
	Shell material	Metal shell, anti-static, anti-magnetic, anti-strong electric field interference